



# SAFETY DATA SHEETS

According to Regulation (EU) No.1907/2006, Regulation (EU) No. 1272/2008 and their subsequent amendments and corrigenda

Version: 1.0  
Creation Date: Nov. 29, 2021  
Revision Date: Nov. 29, 2021

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Product name** Ball-pen ink (BF328-BLACK)  
**Other means of identification**  
**Other names** -  
**Product number** -

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** for writing  
**Uses advised against** no data available  
**Reason why uses advised against** no data available

### 1.3. Details of the supplier of the safety data sheet

**Details of the supplier**  
**Company** COS - Complete Office Supplies  
**Address** 25, NYRANG STREET, LIDCOMBE, NSW, AUSTRALIA, 2141  
**Telephone** +(61)1300-88-22-44  
**Details of the non-Community manufacturer or formulator**  
**Company** COS - Complete Office Supplies  
**Address** 25, NYRANG STREET, LIDCOMBE, NSW, AUSTRALIA, 2141  
**Telephone** +(61)1300-88-22-44  
**E-mail address of competent person responsible for the SDS** category@cos.net.au

### 1.4. Emergency telephone number

**Emergency telephone number** +(61)1300-88-22-44  
**Opening hours** Monday to Friday, 9am-5pm (Standard time zone: UTC/GMT+10 hours).

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### 2.1.1. Classification according to Regulation (EC) No 1272/2008 (CLP)

Acute Tox. 4, H302  
Skin Corr. 1, H314  
Eye Dam. 1, H318  
Skin Sens. 1B, H317  
Aquatic Acute 1, H400  
Aquatic Chronic 1, H410

#### 2.1.2. Additional information

For full text of Hazard- and EU Hazard-statements: see SECTION 16.

### 2.2. Label elements

**Labelling according to Regulation (EC) No 1272/2008 [CLP]**

**Pictogram(s)**



|   |  |
|---|--|
| <b>Signal word</b>                          | Danger   |
| <b>Hazard statement(s)</b>                  | H302 Harmful if swallowed.<br>H314 Causes severe skin burns and eye damage.<br>H318 Causes serious eye damage.<br>H317 May cause an allergic skin reaction.<br>H400 Very toxic to aquatic life.<br>H410 Very toxic to aquatic life with long lasting effects.  |
| <b>Precautionary statement(s)</b>           | P260 Do not breathe dust/fume/gas/mist/vapours/spray.<br>P273 Avoid release to the environment.<br>P280 Wear protective gloves/protective clothing/eye protection/face protection.<br>P391 Collect spillage.<br>P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].<br>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| <b>Supplemental Hazard information (EU)</b> | no data available  |

### 2.3. Other hazards

no data available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

| Chemical name  | Common names and synonyms | CAS number | EC number | Registration number | Classification according to Regulation (EC)No 1278/2008(CLP)                                       | Concentration |
|--|---------------------------|------------|-----------|---------------------|--|---------------|
| 2-phenoxyethanol   | 2-Phenoxy Ethanol         | 122-99-6   | 204-589-7 | -                   | Acute Tox. 4,H302;Eye Irrit. 2,H319  | 30%           |
| [4-[p,p'-bis(dimethylamino)benzhydrylidene]cyclohexa-2,5-dien-1-ylidene]dimethylammonium m-[[p-anilinophenyl]azo]benzenesulphonate | solvent black 46          | 65113-55-5 | 265-449-9 | -                   | Skin Sens. 1B,H317;Eye Dam. 1,H318;STOT SE 3,H335,H336;Aquatic Acute 1,H400;Aquatic Chronic 1,H410 | 25%           |
| Benzyl alcohol   | Benzy1 alcohol            | 100-51-6   | 202-859-9 | -                   | Acute Tox. 4,H302;Acute Tox. 4,H332  | 15%           |
| [Name confidential or not available]   | Keton resin               | 25054-06-2 | 607-515-5 | -                   | Not classified.  | 15%           |
| [Name confidential or not available]   | Epoxy resin               | 24969-06-0 | 607-468-0 | -                   | Not classified.  | 10%           |
| 2,2',2"-nitritoltriethanol   | Triethanolamine           | 102-71-6   | 203-049-8 | -                   | Not classified.  | 5%            |

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General notes

Medical attention is required. Consult a doctor. Show this safety data sheet (SDS) to the doctor in attendance.

#### Following inhalation

Fresh air, rest.

#### In case of skin contact

Rinse and then wash skin with water and soap.

#### In case of eye contact

First rinse with plenty of water for several minutes (remove contact lenses if easily possible), then refer for medical attention.

#### If swallowed

Rinse mouth. Give one or two glasses of water to drink. Refer for medical attention .

### 4.2. Most important symptoms and effects, both acute and delayed

May cause moderate eye irritation and moderate corneal injury. Excessive exposure may cause skin irritation and hemolysis. (USCG, 1999)

#### **4.3. Indication of any immediate medical attention and special treatment needed**

Immediate first aid: Ensure that adequate decontamination has been carried out. If patient is not breathing, start artificial respiration, preferably with a demand valve resuscitator, bag-valve-mask device, or pocket mask, as trained. Perform CPR if necessary. Immediately flush contaminated eyes with gently flowing water. Do not induce vomiting. If vomiting occurs, lean patient forward or place on the left side (head-down position, if possible) to maintain an open airway and prevent aspiration. Keep patient quiet and maintain normal body temperature. Obtain medical attention. Poisons A and B

---

### **SECTION 5: Firefighting measures**

#### **5.1. Extinguishing media**

##### **Suitable extinguishing media**

To fight fire, use CO<sub>2</sub>, dry chemical.

#### **5.2. Special hazards arising from the substance or mixture**

Combustible.

#### **5.3. Advice for firefighters**

Use water spray, powder, alcohol-resistant foam, carbon dioxide.

---

### **SECTION 6: Accidental release measures**

#### **6.1. Personal precautions, protective equipment and emergency procedures**

Personal protection: filter respirator for organic gases and vapours adapted to the airborne concentration of the substance. Collect leaking liquid in sealable containers. Absorb remaining liquid in sand or inert absorbent. Then store and dispose of according to local regulations.

#### **6.2. Environmental precautions**

Personal protection: filter respirator for organic gases and vapours adapted to the airborne concentration of the substance. Collect leaking liquid in sealable containers. Absorb remaining liquid in sand or inert absorbent. Then store and dispose of according to local regulations.

#### **6.3. Methods and materials for containment and cleaning up**

Collect and arrange disposal. Keep the chemical in suitable and closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment. Adhered or collected material should be promptly disposed of, in accordance with appropriate laws and regulations.

#### **6.4. Reference to other sections**

For disposal suggestions see section 13. For exposure controls / personal protection suggestions see section 8.

---

### **SECTION 7: Handling and storage**

#### **7.1. Precautions for safe handling**

NO open flames.

#### **7.2. Conditions for safe storage, including any incompatibilities**

Separated from strong oxidants.

#### **7.3. Specific end use(s)**

Main uses of the chemical are mentioned in section 1.2. No other specific uses are stipulated.

---

### **SECTION 8: Exposure controls/personal protection**

#### **8.1. Control parameters**

##### **Occupational Exposure limit values**

MAK: 5.7 mg/m<sup>3</sup>, 1 ppm; peak limitation category: I(1); pregnancy risk group: C

#### **8.2. Exposure controls**

##### **8.2.1. Appropriate engineering controls**

Ensure adequate ventilation. Handle in accordance with good industrial hygiene and safety practice. Set up emergency exits and the risk-elimination area.

##### **8.2.2. Individual protection measures, such as personal protective equipment**

###### **Eye/face protection**

Wear tightly fitting safety goggles with side-shields conforming to EN 166(EU) or NIOSH (US).

###### **Skin protection**

Wear fire/flame resistant and impervious clothing. Handle with gloves. Gloves must be inspected prior to use. Wash and dry hands.

###### **Respiratory protection**

If the exposure limits are exceeded, irritation or other symptoms are experienced, use a full-face respirator.

###### **Thermal hazards**

no data available

### 8.2.3. Environmental exposure controls

See section 6.2.

---

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

|   |  |
|---|--|
| <b>Appearance</b>                                   | Liquid.  |
| <b>Odour</b>  | pure CAS 122-99-6: Faint aromatic odor;pure CAS 100-51-6: Faint aromatic odor;pure CAS 102-71-6: Slight ammonical odor   |
| <b>Odour threshold</b>                              | pure CAS 100-51-6: 5.5 ppm   |
| <b>pH</b>   | pure CAS 65113-55-5: 7.3.;pure CAS 100-51-6: A solution in water is neutral to litmus;pure CAS 102-71-6: pH = 10.5 (0.1 N aqueous solution); strong base   |
| <b>Melting point/freezing point</b>                 | pure CAS 122-99-6: 14°C;pure CAS 65113-55-5: Atm. press.:1 013 hPa. Remarks:The test item shows no melting point. No liquid phase at no point but a softening phase from 180°C, and start decomposing > 200°C.;pure CAS 100-51-6: -15°C;pure CAS 102-71-6: 21.6°C  |
| <b>Initial boiling point and boiling range</b>      | pure CAS 122-99-6: 245°C;pure CAS 100-51-6: 205°C;pure CAS 25054-06-2: 155.7°C at 760mmHg;pure CAS 102-71-6: 335.4°C   |
| <b>Flash point</b>                                  | 105  |
| <b>Evaporation rate</b>                             | no data available  |
| <b>Flammability</b>                                 | pure CAS 122-99-6: Combustible.;pure CAS 100-51-6: Combustible.;pure CAS 102-71-6: Combustible. Gives off irritating or toxic fumes (or gases) in a fire.  |
| <b>Upper/lower flammability or explosive limits</b> | no data available  |
| <b>Vapour pressure</b>                              | pure CAS 122-99-6: 0.0013 kPa(20°C);pure CAS 100-51-6: 13.2 Pa(20°C);pure CAS 102-71-6: <1 Pa(25°C)  |
| <b>Vapour density</b>                               | pure CAS 122-99-6: 4.8 (vs air);pure CAS 100-51-6: 3.7 (vs air);pure CAS 102-71-6: 5.14 (vs air)   |
| <b>Relative density</b>                             | pure CAS 122-99-6: 1.1;pure CAS 65113-55-5: 0.69. Temperature:20 °C.;pure CAS 100-51-6: 1.04;pure CAS 24969-06-0: 1.36 g/mL at 25 °C(lit.);pure CAS 102-71-6: 1.1  |
| <b>Solubility(ies)</b>                              | pure CAS 122-99-6: Solubility in water, g/100ml: 2.7 ;pure CAS 65113-55-5: In water: < 0.01 mg/L. Temperature:25 °C. Remarks:PH not mentionned in the study.;pure CAS 100-51-6: Solubility in water, g/100ml: 4 ;pure CAS 102-71-6: Solubility in water: miscible  |
| <b>Partition coefficient n-octanol/water</b>        | pure CAS 122-99-6: 1.2;pure CAS 65113-55-5: log Pow = >= 5.7. Temperature:22 °C. Remarks:The log Kow is between 5.7 and the infinity since the hydrosolubility tends toward 0.;pure CAS 100-51-6: 1.1;pure CAS 102-71-6: -2.3 (not explosive)  |
| <b>Auto-ignition temperature</b>                    | pure CAS 122-99-6: 500°C;pure CAS 65113-55-5: <= 370 °C. Remarks:Preliminary test.;pure CAS 100-51-6: 436°C;pure CAS 102-71-6: 324°C   |
| <b>Decomposition temperature</b>                    | no data available  |
| <b>Viscosity</b>                                    | pure CAS 122-99-6: dynamic viscosity (in mPa s) = 41. Temperature:19.8°C. Remarks:Temperature in the range 19.5-20.2 °C. Viscosity independent of the shear rate.;dynamic viscosity (in mPa s) = 19. Temperature:40.5°C. Remarks:Temperature in the range 40-41 °C. Viscosity independent of the shear rate.;pure CAS 100-51-6: dynamic viscosity (in mPa s) = 5.05. Temperature:25.0°C.;pure CAS 102-71-6: kinematic viscosity (in mm²/s) = 830.2. Temperature:20°C.;kinematic viscosity (in mm²/s) = 181.5. Temperature:40°C.;kinematic viscosity (in mm²/s) = 59.1. Temperature:60.0°C. |
| <b>Explosive properties</b>                         | no data available  |
| <b>Oxidising properties</b>                         | no data available  |

### 9.2. Other information

no data available

---

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Reacts with strong oxidants.

### 10.2. Chemical stability

Stable in presence of acids & alkalies.

### 10.3. Possibility of hazardous reactions

Reacts with strong oxidants.

### 10.4. Conditions to avoid

no data available

### 10.5. Incompatible materials

Can react vigorously with oxidizing materials.

### 10.6. Hazardous decomposition products

When heated to decomposition it emits acrid smoke and irritating fumes.

---

## SECTION 11: Toxicological information

## 11.1. Information on toxicological effects

### Acute toxicity

- Oral: pure CAS 122-99-6: LD50 - rat (female) - 1 840 mg/kg bw.;pure CAS 65113-55-5: LD50 - rat (female) - > 2 000 mg/kg bw.;pure CAS 100-51-6: LD50 - rat (male) - 1.55 mL/kg bw. Remarks:Corresponding to 1620 mg/kg bw (density: 1.045 g/mL);pure CAS 102-71-6: LD50 - rat (male/female) - 6 400 mg/kg bw.
- Inhalation: pure CAS 122-99-6: LC50 - rat (male/female) - > 1 000 mg/m<sup>3</sup> air (nominal);pure CAS 100-51-6: LC50 - rat (male/female) - > 4 178 mg/m<sup>3</sup> air.;pure CAS 102-71-6: LC0 - rat (male/female) - saturated TEA atmosphere (approximately 1.8 mg/m<sup>3</sup>).
- Dermal: pure CAS 122-99-6: LD50 - rat (male/female) - 14 391 mg/kg bw.;pure CAS 65113-55-5: LD50 - rat (male) - > 2 000 mg/kg bw.;pure CAS 100-51-6: LD50 - guinea pig - < 5 000 mg/kg bw.;pure CAS 102-71-6: LD50 - rabbit - > 2 000 mg/kg bw.

### Skin corrosion/irritation

no data available

### Serious eye damage/irritation

no data available

### Respiratory or skin sensitization

no data available

### Germ cell mutagenicity

no data available

### Carcinogenicity

no data available

### Reproductive toxicity

no data available

### STOT-single exposure

pure CAS 122-99-6: The substance is irritating to the eyes, skin and respiratory tract. The substance may cause effects on the central nervous system and peripheral nervous system. This may result in impaired functions.;pure CAS 100-51-6: The aerosol is irritating to the eyes and skin. The substance may cause effects on the nervous system.;pure CAS 102-71-6: The substance is irritating to the eyes, skin and respiratory tract.

### STOT-repeated exposure

pure CAS 122-99-6: The substance defats the skin, which may cause dryness or cracking. The substance may have effects on the central nervous system. This may result in impaired functions.;pure CAS 100-51-6: Repeated or prolonged contact may cause skin sensitization.;pure CAS 102-71-6: Repeated or prolonged contact may cause skin sensitization.

### Aspiration hazard

pure CAS 122-99-6: A harmful contamination of the air will not or will only very slowly be reached on evaporation of this substance at 20°C.;pure CAS 100-51-6: No indication can be given about the rate at which a harmful concentration of this substance in the air is reached on evaporation at 20°C.;pure CAS 102-71-6: Evaporation at 20°C is negligible; a harmful concentration of airborne particles can, however, be reached quickly when dispersed.

---

## SECTION 12: Ecological information

### 12.1. Toxicity

- Toxicity to fish: pure CAS 122-99-6: LC50 - Pimephales promelas - 344 mg/L - 96 h.;pure CAS 100-51-6: LC50 - Pimephales promelas - 460 mg/L - 96 h.;pure CAS 102-71-6: LC50 - Pimephales promelas - 11 800 mg/L - 96 h.
- Toxicity to daphnia and other aquatic invertebrates: pure CAS 122-99-6: EC50 - Daphnia magna - > 500 mg/L - 48 h.;pure CAS 65113-55-5: EC50 - Daphnia magna - ca. 0.011 mg/L - 48 h.;pure CAS 100-51-6: EC50 - Daphnia magna - 230 mg/L - 48 h.;pure CAS 102-71-6: EC50 - Ceriodaphnia dubia - 609.88 mg/L - 48 h.
- Toxicity to algae: pure CAS 122-99-6: EC50 - Desmodesmus subspicatus (previous name: Scenedesmus subspicatus) - > 500 mg/L - 72 h.;pure CAS 65113-55-5: EC50 - Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum) - ca. 0.005 mg/L - 72 h.;pure CAS 100-51-6: EC50 - Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum) - 770 mg/L - 72 h.;pure CAS 102-71-6: EC50 - Desmodesmus subspicatus (previous name: Scenedesmus subspicatus) - 512 mg/L - 72 h.
- Toxicity to microorganisms: pure CAS 122-99-6: EC20 - activated sludge of a predominantly domestic sewage - 620 mg/L - 30 min. Remarks:Respiration rate.;pure CAS 100-51-6: IC50 - Aerobic heterotrophs and Nitrosomonas - 2 100 mg/L - 49 h. Remarks:Respiration rate.;pure CAS 102-71-6: IC50 - activated sludge of a predominantly domestic sewage - > 1 000 mg/L - 3 h. Remarks:Respiration rate.

### 12.2. Persistence and degradability

AEROBIC: For 2-phenoxyethanol, theoretical BODs of 2% (5-day), 71% (10-day), and 80% (20-day) have been measured(1); a theoretical 20-day BOD of 50% indicates a compound will largely be removed during biological waste treatment(1).

### 12.3. Bioaccumulative potential

An estimated BCF of 1.5 was calculated in fish for 2-phenoxyethanol(SRC), using a log Kow of 1.16(1) and a regression-derived equation(2). According to a classification scheme(3), this BCF suggests the potential for bioconcentration in aquatic organisms is low(SRC).

### 12.4. Mobility in soil

Using a structure estimation method based on molecular connectivity indices(1), the Koc of 2-phenoxyethanol can be estimated to be 15(SRC). According to a classification scheme(2), this estimated Koc value suggests that 2-phenoxyethanol is expected to have very high mobility in soil.

### 12.5. Results of PBT and vPvB assessment

no data available

## 12.6. Other adverse effects

no data available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### Product

The material can be disposed of by removal to a licensed chemical destruction plant or by controlled incineration with flue gas scrubbing. Do not contaminate water, foodstuffs, feed or seed by storage or disposal. Do not discharge to sewer systems.

#### Contaminated packaging

Containers can be triply rinsed (or equivalent) and offered for recycling or reconditioning. Alternatively, the packaging can be punctured to make it unusable for other purposes and then be disposed of in a sanitary landfill. Controlled incineration with flue gas scrubbing is possible for combustible packaging materials.

## SECTION 14: Transport information

### 14.1. UN number

ADR/RID: Not dangerous goods.

IMDG: Not dangerous goods.

IATA: Not dangerous goods.

### 14.2. UN Proper Shipping Name

ADR/RID: Not dangerous goods.

IMDG: Not dangerous goods.

IATA: Not dangerous goods.

### 14.3. Transport hazard class(es)

ADR/RID: Not dangerous goods.

IMDG: Not dangerous goods.

IATA: Not dangerous goods.

### 14.4. Packing group

ADR/RID: Not dangerous goods.

IMDG: Not dangerous goods.

IATA: Not dangerous goods.

### 14.5. Environmental hazards

ADR/RID: Yes

IMDG: Yes

IATA: Yes

### 14.6. Special precautions for user

no data available

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

no data available

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

| Chemical name  | Common names and synonyms | CAS number | EC number   |
|--|---------------------------|------------|-------------|
| 2-phenoxyethanol   | 2-Phenoxy Ethanol         | 122-99-6   | 204-589-7   |
| European Inventory of Existing Commercial Chemical Substances (EINECS)   |                           |            | Listed.     |
| Chemical name  | Common names and synonyms | CAS number | EC number   |
| [4-[p,p'-bis(dimethylamino)benzhydrylidene]cyclohexa-2,5-dien-1-ylidene]dimethylammonium m-[[p-anilinophenyl]azo]benzenesulphonate | solvent black 46          | 65113-55-5 | 265-449-9   |
| European Inventory of Existing Commercial Chemical Substances (EINECS)   |                           |            | Listed.     |
| Chemical name  | Common names and synonyms | CAS number | EC number   |
| Benzyl alcohol   | Benzyl alcohol            | 100-51-6   | 202-859-9   |
| European Inventory of Existing Commercial Chemical Substances (EINECS)   |                           |            | Listed.     |
| Chemical name  | Common names and synonyms | CAS number | EC number   |
| [Name confidential or not available]   | Keton resin               | 25054-06-2 | 607-515-5   |
| European Inventory of Existing Commercial Chemical Substances (EINECS)   |                           |            | Not Listed. |
| Chemical name  | Common names and synonyms | CAS number | EC number   |
| [Name confidential or not available]   | Epoxy resin               | 24969-06-0 | 607-468-0   |
| European Inventory of Existing Commercial Chemical Substances (EINECS)   |                           |            | Not Listed. |
| Chemical name  | Common names and synonyms | CAS number | EC number   |
| 2,2',2''-nitrioltriethanol   | Triethanolamine           | 102-71-6   | 203-049-8   |
| European Inventory of Existing Commercial Chemical Substances (EINECS)   |                           |            | Listed.     |

### 15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

## SECTION 16: Other information

## Indication of changes

**Version 1.0**

Initial issue.

## Abbreviations and acronyms

- CAS: Chemical Abstracts Service
- ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
- RID: Regulation concerning the International Carriage of Dangerous Goods by Rail
- IMDG: International Maritime Dangerous Goods
- IATA: International Air Transportation Association
- TWA: Time Weighted Average
- STEL: Short term exposure limit
- LC50: Lethal Concentration 50%
- LD50: Lethal Dose 50%
- EC50: Effective Concentration 50%

## Key literature references and sources for data

- IPCS - The International Chemical Safety Cards (ICSC), website: <http://www.ilo.org/dyn/icsc/showcard.home>
- HSDB - Hazardous Substances Data Bank, website: <https://toxnet.nlm.nih.gov/newtoxnet/hsdb.htm>
- IARC - International Agency for Research on Cancer, website: <http://www.iarc.fr/>
- eChemPortal - The Global Portal to Information on Chemical Substances by OECD, website: [http://www.echemportal.org/echemportal/index?pageID=0&request\\_locale=en](http://www.echemportal.org/echemportal/index?pageID=0&request_locale=en)
- CAMEO Chemicals, website: <http://cameochemicals.noaa.gov/search/simple>
- ChemIDplus, website: <http://chem.sis.nlm.nih.gov/chemidplus/chemidlite.jsp>
- ERG - Emergency Response Guidebook by U.S. Department of Transportation, website: <http://www.phmsa.dot.gov/hazmat/library/erg>
- Germany GESTIS-database on hazard substance, website: <http://www.dguv.de/ifa/gestis/gestis-stoffdatenbank/index-2.jsp>
- ECHA - European Chemicals Agency, website: <https://echa.europa.eu/>

## Full text of H-Statements referred to under sections 2 and/or 3.

|                               |  |
|-------------------------------|--|
| <b>Acute Tox. 4,H302</b>      | Acute toxicity - Oral, Category 4  |
| <b>Skin Corr. 1,H314</b>      | Skin corrosion, Category 1   |
| <b>Eye Dam. 1,H318</b>        | Serious eye damage, Category 1   |
| <b>Skin Sens. 1B,H317</b>     | Skin sensitization, Sub-category 1B  |
| <b>Aquatic Acute 1,H400</b>   | Hazardous to the aquatic environment, short-term (Acute) - Category Acute 1    |
| <b>Aquatic Chronic 1,H410</b> | Hazardous to the aquatic environment, long-term (Chronic) - Category Chronic 1 |
| <b>H302</b>                   | Harmful if swallowed.  |
| <b>H314</b>                   | Causes severe skin burns and eye damage.                                       |
| <b>H318</b>                   | Causes serious eye damage.   |
| <b>H317</b>                   | May cause an allergic skin reaction.   |
| <b>H400</b>                   | Very toxic to aquatic life.  |
| <b>H410</b>                   | Very toxic to aquatic life with long lasting effects.                          |

## Advice on any training appropriate for workers to ensure protection of human health and the environment

Provide sufficient information, guidance and training to operating personnel.

## Other Information

The relation between odour and the occupational exposure limit cannot be indicated.

**Any questions regarding this SDS, Please send your inquiry to [sds@xixisys.com](mailto:sds@xixisys.com)**

---

*Disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. We as supplier shall not be held liable for any damage resulting from handling or from contact with the above product.*