according to 1907/2006/EC, Article 31



Page 1/7 Printing date 19.04.2021 Revision: 19.04.2021 Version number 20

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

- · 1.1 Product identifier
- · Trade name: MA 4511 black
- · Article number: 100000001126
- · Registration number

The ingredients of this product meet the criteria of the Regulation 1907/2006/EC (REACH).

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

Currently no such applications are identified.

- · Application of the substance / the mixture alcohol based permanent marking ink
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

COS - Complete Office Supplies 25, NYRANG STREET, LIDCOMBE NSW, AUSTRALIA, 2141 Phone + 61 1300-88-22-44 Fax + 61 1300-73-88-20 www.cos.net.au

· Further information obtainable from:

Technical Service & Product Safety Tel.: +49-621-37702 390 E-Mail: msds@dokumental.de

1.4 Emergency telephone number:

GBK Gefahrgut Büro GmbH +49 (0) 6132 / 84463 Ingelheim, Deutschland

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS08 health hazard

H341 Suspected of causing genetic defects.



GHS05 corrosion

H318 Causes serious eye damage. Eye Dam. 1



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 $\,$ H412 $\,$ Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms









GHS02

GHS05

· Signal word Danger

· Hazard-determining components of labelling:

Phosphoric acid mono-bis-(2-ethylhexyl)-ester 1-methoxy-2-propanol C.I. Solvent Orange 3

Page 2/7

(Contd. of page 1)

Trade name: MA 4511 black

· Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H341 Suspected of causing genetic defects.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. P321 Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse. P362+P364

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Additional information:

EUH208 Contains C.I. Solvent Blue 4 < 0,1% Michler's Ketone. May produce an allergic reaction.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable. · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

CAS: 64-17-5	ethanol	50-100%
EINECS: 200-578-6 Reg.nr.: 01-2119457610-43	🔖 Flam. Liq. 2, H225; 🐧 Eye Irrit. 2, H319	
CAS: 107-98-2 EINECS: 203-539-1 Reg.nr.: 01-2119457435-35	1-methoxy-2-propanol → Flam. Liq. 3, H226; → STOT SE 3, H336	10-25%
CAS: 12645-31-7 EINECS: 235-741-0 Reg.nr.: 01-2119896587-13	Phosphoric acid mono-bis-(2-ethylhexyl)-ester Skin Corr. 1B, H314	2.5-10%
CAS: 561-41-1 EINECS: 209-218-2 Reg.nr.: 01-2119979581-25	C.I. Solvent Violet 8 Alternative CAS number: 52080-58-7 Acute Tox. 4, H302; Eye Irrit. 2, H319; Aquatic Chronic 3, H412	≤ 2.5%
CAS: 495-54-5 EINECS: 207-803-7 Reg.nr.: 01-2120754909-37	C.I. Solvent Orange 3 Muta. 2, H341; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute Tox. 4, H302; Skin Irrit. 2, H315	≤ 2.5%
CAS: 6786-83-0 EINECS: 229-851-8 Reg.nr.: 01-2119950688-22	C.I. Solvent Blue 4 < 0,1% Michler's Ketone	≤ 1 %

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation:

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

 \cdot 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· 5.2 Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 3)

according to 1907/2006/EC, Article 31



Page 3/7 Printing date 19.04.2021 Revision: 19.04.2021 Version number 20

Trade name: MA 4511 black

· 5.3 Advice for firefighters

· Protective equipment: No special measures required.

(Contd. of page 2)

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away. Wear protective clothing.

6.2 Environmental precautions:

Prevent seepage into sewage system, workpits and cellars.

Inform respective authorities in case of seepage into water course or sewage system.

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

\cdot 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Additional information about design of technical facilities: No further data; see item 7.
- · Ingredients with limit values that require monitoring at the workplace:

107-98-2 1-methoxy-2-propanol (10-25%)

Short-term value: 568 mg/m³, 150 ppm TOFIVLong-term value: 375 mg/m³, 100 ppm Skin

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

(Contd. on page 4)

Page 4/7 Printing date 19.04.2021 Revision: 19.04.2021 Version number 20

Trade name: MA 4511 black

(Contd. of page 3)

Selection of the glove material on consideration of the penetration times, rates of diffusion and the

If only a short-term loading of the glove material by splashes is expected, tricoted gloves with higher wearability for the better acceptance of the users are recommended.

· Material of gloves

 $\textit{The selection of the suitable gloves does not only depend on the material, but also on further \textit{marks} } \\$ of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. Nitrile rubber, NBR

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

SECTION 9: Physical and chemical properties		
· 9.1 Information on basic physical and chemical properties · General Information		
Appearance:		
Form:	Fluid	
Colour:	According to product specification	
Odour:	Product specific	
Odour threshold:	Not determined.	
Important information on protection of health a environment, and on safety.	and _	
pH-value at 20 °C:	5.5	
Change in condition		
Melting point/freezing point:	Undetermined.	
Initial boiling point and boiling range:	78 °C	
Flash point:	13 °C	
Flammability (solid, gas):	Not applicable.	
Ignition temperature:	287 °C	
Decomposition temperature:	Not determined.	
Auto-ignition temperature:	Product is not selfigniting.	
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.	
Explosion limits:		
Lower:	1.5 Vol %	
Upper:	15 Vol %	
Vapour pressure at 20 °C:	59 hPa	
Density:	Not determined.	
Relative density	Not determined.	
Vapour density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
water:	Fully miscible.	
Partition coefficient: n-octanol/water:	Not determined.	
Viscosity:		
Dynamic at 20 °C:	2.2 mPas	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	87.2 %	
Solids content:	8.4 %	

according to 1907/2006/EC, Article 31

okumental power your pen

Page 5/7
Printing date 19.04.2021
Revision: 19.04.2021
Version number 20

Trade name: MA 4511 black

(Contd. of page 4)

· 9.2 Other information

The physical and chemical properties given in Section 9.1 are rough data only, which are partially derived from the component's data of the mixture. These data are no binding product specifications.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

12645-31-7 Phosphoric acid mono-bis-(2-ethylhexyl)-ester

Oral LD50 3,000 mg/kg (rat)

- · Primary irritant effect:
- · Skin corrosion/irritation
- Causes skin irritation.
- · Serious eye damage/irritation
 - Causes serious eye damage.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- \cdot CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity
- Suspected of causing genetic defects.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure
 - May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- \cdot 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water Do not allow product to reach ground water, water course or sewage system, even in small quantities. Danger to drinking water if even extremely small quantities leak into the ground. Harmful to aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 6)



according to 1907/2006/EC, Article 31

Trade name: MA 4511 black

	(G	onta. or page 5)
· European w	raste catalogue	
08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (P. VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS	PAINTS,
08 01 00	wastes from MFSU and removal of paint and varnish	
08 01 13*	sludges from paint or varnish containing organic solvents or other hazardous s	ubstances

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.
- $\cdot \ \textbf{Recommended cleansing agents:} \ \textit{Water, if necessary together with cleansing agents.}$

14.1 UN-Number ADR, IMDG, IATA	UN1263
14.2 UN proper shipping name ADR IMDG, IATA	1263 PAINT PAINT
14.3 Transport hazard class(es)	
ADR	
Class	3 (F1) Flammable liquids.
Label	3
Class	3 Flammable liquids.
Label	3
14.4 Packing group ADR, IMDG, IATA	II
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category	Warning: Flammable liquids. 33 F-E, <u>S-E</u> B
14.7 Transport in bulk according to Annex II o	of
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
Transport category	2
Tunnel restriction code	D/E
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 1263 PAINT, 3, II

SECTION 15: Regulatory information

- \cdot 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- \cdot Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- \cdot Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

(Contd. on page 7)

according to 1907/2006/EC, Article 31

okumental power your pen

Page 7/7
Printing date 19.04.2021
Revision: 19.04.2021
Version number 20

Trade name: MA 4511 black

(Contd. of page 6)

- \cdot Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

None of the ingredients is listed.

- · National regulations:
- · Technical instructions (air):

Class	Share in %
NK	50-100

- · Waterhazard class: Water hazard class 3 (Self-assessment): extremely hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

```
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H341 Suspected of causing genetic defects.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.
```

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GRS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
LC50: Lethal concentration, 50 percent
LD50: Lethal concentration, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 2: Flammable liquids - Category 2
Flam. Liq. 3: Flammable liquids - Category 3
Acute Tox. 4: Acute toxicity - Category 4
Skin Corr. 1B: Skin corrosion/irritation - Category 1
Skin IIIT. 2: Skin corrosion/irritation - Category 2
Eye Dam. 1: Serious eye damage/eye irritation - Category 1
Skin Sens. 1B: Skin sensitisation - Category 1
Skin Sens. 1B: Skin sensitisation - Category 1
Skin Sens. 1B: Skin sensitisation - Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

 \cdot * Data compared to the previous version altered.