

1. Device Name	NITRILE BLAX HD																																			
2. Description	Powder free 100% nitrile, Beaded Cuff, Industrial trade quality, On-Line Chlorinated, Ambidextrous, Non Sterile, Raised diamond grip, Free from Vinyl, BPA, Phthalates and MBT.																																			
3. Product Codes & Sizes	<table border="1"> <thead> <tr> <th>Product Code</th> <th>Size</th> <th>Inner Barcode</th> <th>Shipper Barcode</th> </tr> </thead> <tbody> <tr> <td>41162</td> <td>MEDIUM</td> <td>9311059411626</td> <td>19311059411623</td> </tr> <tr> <td>41163</td> <td>LARGE</td> <td>9311059411633</td> <td>19311059411630</td> </tr> <tr> <td>41164</td> <td>XL</td> <td>9311059411640</td> <td>19311059411647</td> </tr> <tr> <td>41165</td> <td>XXL</td> <td>9311059411657</td> <td>19311059411654</td> </tr> </tbody> </table>				Product Code	Size	Inner Barcode	Shipper Barcode	41162	MEDIUM	9311059411626	19311059411623	41163	LARGE	9311059411633	19311059411630	41164	XL	9311059411640	19311059411647	41165	XXL	9311059411657	19311059411654												
Product Code	Size	Inner Barcode	Shipper Barcode																																	
41162	MEDIUM	9311059411626	19311059411623																																	
41163	LARGE	9311059411633	19311059411630																																	
41164	XL	9311059411640	19311059411647																																	
41165	XXL	9311059411657	19311059411654																																	
4. Recommended Applications	<ul style="list-style-type: none"> Medical Industrial Manufacturing Plumbing Petroleum Industry Mechanics Oil Refinery Food Manufacturing Cleaning Laboratory Pharmaceutical Cosmetic Tattooists Childcare Hair & Beauty 																																			
5. Materials	Nitrile,																																			
6. Production Process	Former cleaning and washing, coagulant dipping, coagulant drying, nitrile dipping, nitrile gelling oven, beading, leaching tank dip, main curing oven, cooling tank, chlorination tank, soak rinse tank, neutralizer, post leaching tank, blower, stripping, QC inspection, packing, Pre-shipment inspection.																																			
7. Standards & Approvals	<div style="display: flex; align-items: center;"> <div style="margin-right: 20px;"> <p>EN ISO 374-5</p> <p>VIRUS</p> </div> <div style="margin-right: 20px;"> <p>EN374</p> <p>KPT</p> </div> <div> <p>Nitrile Blax HD is tested to and complies with;</p> <ul style="list-style-type: none"> ASTM D6319-2015 EN 374 EN 455 Entered into the ARTG - ARTG# 402583 Acceptable Quality Level AQL1.5 </div> </div>																																			
8. Dimensions	<table border="1"> <thead> <tr> <th>SIZE</th> <th>LENGTH (+/-10)</th> <th>THICKNESS FINGER SINGLE WALL +/-0.02</th> <th>THICKNESS PALM SINGLE WALL +/-0.02</th> <th>PALM WIDTH +/-5mm</th> <th>WEIGHT PER PIECE +/-0.5gm</th> </tr> </thead> <tbody> <tr> <td>MEDIUM</td> <td>240mm</td> <td>0.20mm</td> <td>0.15mm</td> <td>95mm</td> <td>9.0gm</td> </tr> <tr> <td>LARGE</td> <td>240mm</td> <td>0.20mm</td> <td>0.15mm</td> <td>108mm</td> <td>10.0gm</td> </tr> <tr> <td>XL</td> <td>240mm</td> <td>0.20mm</td> <td>0.15mm</td> <td>114mm</td> <td>11.0gm</td> </tr> <tr> <td>XXL</td> <td>240mm</td> <td>0.20mm</td> <td>0.15mm</td> <td>127mm</td> <td>12.0gm</td> </tr> </tbody> </table> <p><i>Note: if Textured gloves then minimum requirements shall be 10% lower than those shown in table.</i></p>						SIZE	LENGTH (+/-10)	THICKNESS FINGER SINGLE WALL +/-0.02	THICKNESS PALM SINGLE WALL +/-0.02	PALM WIDTH +/-5mm	WEIGHT PER PIECE +/-0.5gm	MEDIUM	240mm	0.20mm	0.15mm	95mm	9.0gm	LARGE	240mm	0.20mm	0.15mm	108mm	10.0gm	XL	240mm	0.20mm	0.15mm	114mm	11.0gm	XXL	240mm	0.20mm	0.15mm	127mm	12.0gm
SIZE	LENGTH (+/-10)	THICKNESS FINGER SINGLE WALL +/-0.02	THICKNESS PALM SINGLE WALL +/-0.02	PALM WIDTH +/-5mm	WEIGHT PER PIECE +/-0.5gm																															
MEDIUM	240mm	0.20mm	0.15mm	95mm	9.0gm																															
LARGE	240mm	0.20mm	0.15mm	108mm	10.0gm																															
XL	240mm	0.20mm	0.15mm	114mm	11.0gm																															
XXL	240mm	0.20mm	0.15mm	127mm	12.0gm																															
9. Physical Properties	<table border="1"> <thead> <tr> <th>DESCRIPTION</th> <th>BEFORE AGEING</th> <th>AFTER AGEING</th> </tr> </thead> <tbody> <tr> <td>Elongation at break (%)</td> <td>500% (min)</td> <td>400% (min)</td> </tr> <tr> <td>Tensile Strength (MPa)</td> <td>14.0 MPa (min)</td> <td>14.0 MPa (min)</td> </tr> </tbody> </table>						DESCRIPTION	BEFORE AGEING	AFTER AGEING	Elongation at break (%)	500% (min)	400% (min)	Tensile Strength (MPa)	14.0 MPa (min)	14.0 MPa (min)																					
DESCRIPTION	BEFORE AGEING	AFTER AGEING																																		
Elongation at break (%)	500% (min)	400% (min)																																		
Tensile Strength (MPa)	14.0 MPa (min)	14.0 MPa (min)																																		



10.
Colour

Black

11.
Performance
Requirements

Gloves shall be sampled and inspected in accordance with ISO 2859-1. The inspection levels and acceptable quality limits (AQLs) shall conform to those listed in below table for the characteristics listed.

CHARACTERISTICS	INSPECTION LEVEL	ACCEPTABLE QUALITY LEVEL	REFERENCE STANDARD
Physical Dimensions	S2	4.0	ASTM D6319-10
Physical Properties	S2	4.0	ASTM D6319-10
Pinhole	G1	1.5	ASTM D6319-10
Visual Defects: Major Minor	G1	2.5 4.0	Manufacturers Practice
Packaging Defects Regulatory Visual Critical (Incl Glove Count)	G1 G1 S2	?	In House Inspection
Powder Free Residue	N=5	-	ASTM D6319-10 ASTM D6124-06(2011)

Notes: ** indicates unacceptable at any level For Dimensions and Physical Properties a median of 13 test pieces used as per EN455-2:2015

12.
Quality
Control
Inspection
Procedures

- Shipment is placed in quarantine area separately from other gloves in warehouse as one lot
- Shipment is then sorted by sizes if shipment consists of more than one size.
- QC inspector records lot number(s) indicted on inner boxes and outer cases, sizes quantity of shipment, buyer, date, etc
- QC inspector selects at random samples according to ISO procedures for sampling, each lots of different sizes are handled separately
- Samples are sent for testing as per requirements
- Results of tests will be recorded and only those that meet acceptance criteria are released for dispatch. If shipment consists of more than one size, shipment will be released only when all lots of different sizes have passed.
- If a shipment is found to fail test requirements it will be rejected by QC inspector and not released for shipment.

13.
Packaging

50 pieces will be packed into a dispenser box. The number contained in each dispenser box determined by count. 10 dispenser boxes are packed in 2 layers of 5 giving 10 dispenser boxes inside export quality shipper carton (outer).

14.
Shipper
Carton
Specifications

SIZE	LENGTH (mm)	WIDTH (mm)	HEIGHT (mm)	GROSS WEIGHT (kg)
MEDIUM	368mm	264mm	253mm	2.3kg
LARGE	368mm	264mm	253mm	2.5kg
XL	368mm	264mm	253mm	2.75kg
XXL	368mm	264mm	253mm	3kg

- 15. Storage Conditions** The gloves will maintain their properties when stored in dry conditions out of direct sunlight at between 10°C to 35°C.
-
- 16. Shelf Life** The gloves shall have a shelf life of 5 years from the date of manufacture when stored in compliance with the above storage conditions.