

uvex Hearing Protection System

Ear Muffs

uvex-K3

- AS/NZS 1270:2002 approved
 - SLC80 33dB
 - Class 5
- Weight - 295g
- Dual suspension headband system
- Clamping force of 13.6 Newtons
- Memory foam ear cushions
- Replacement hygiene kit available



uvex Point of Difference	Benefits
Soft padded headband	Optimum ventilation and comfort
SLC80 33dB Class 5	Provides protection and comfort without the issues of isolation and miscommunication
Stainless steel suspension headband system	Provides optimum fit and wearer comfort

Target Applications (but not limited to):

- Industrial plants with high level noise areas and long term noise exposure
- Manufacturer/site or industry with temporary noise

Attenuation data:

Frequency in Hertz	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz
Mean	19.6	21.7	33.6	38.4	37.7	37.3	41.1
STD. Deviation	2.6	2.9	2.5	2.9	2.9	2.7	2.6
Mean minus SD	17.0	18.8	31.1	35.5	34.8	34.6	38.5

Part Numbers & Packaging:

- Part No. 2610.003
- 1 per box
- 20 units per carton

Barcodes:

- 2610.003 - 4031101638133