

SINGLE DOUBLE LEG WEBBING LANYARD

PART CODE: **WLO1**

PRODUCT INFORMATION >

2 metre Webbing Lanyard

WLO1- Single Leg Webbing Lanyard + hardware (Refer to Single Leg Lanyard Hardware Page).

PRODUCT FEATURES >

- An exclusive Extended Length Energy Absorber (ELEA) designed to protect a worker of up to 160kg, including tools and equipment.
- Drop forged lanyard hardware.
- Stitching patterns are sewn by computer controlled bar tacking machinery for precision using UV resistant high tenacity polyester yarn with 100 newton (10kg) breaking strength.
- Unique THETA stitch pattern has over 423 stitches resulting in a seam that matches the lanyard's webbing strength of 3.3t, ensuring no weak point in the lanyard assembly.

PRODUCT DETAILS >

- AUS/NZ designed and engineered.
- High Tenacity webbing 33kN, 220% in excess of AS/NZS 1891.1 requirements.
- Contrast stitch thread colour for easy inspection.
- Standard LINQ shock absorber is rated for wearer of up to 160kg, including tooling and equipment.
- Drop forged D Transition point doubles as a spare leg stowage point.
- Custom lengths available on request, for example: 1.0m, 1.2m, 1.5m, 1.8m
- **Webbing Material:** Polyester; 45mm; UV Resilient; Solvent Resistant.
- **Fall Arrest Hardware:** Drop Forged corrosion resistant electrophoresis; high strength alloy steel.
- **Stitch Pattern:** THETA Pattern combines 423 stitches to exceed 33kN of strength; AS/NZ compliant colour contrast.
- **Web Tenacity:** Min 30kN Max 33kN.

STANDARDS >

EXCEEDS



Australian Standard
AS/NZS 1891.1:2007
Lic: 21481
SAI Global



AS/NZS 1891.1:2007
BMP 713822
BMP 713823
Australian Standard



Reading of LINQ instruction manual prior to use is mandatory. Description and specification subject to change without notice. If in doubt please contact the LINQ helpline.

AUS: 1300 546 747

NZ: 0800 546 747

INTERNATIONAL: +61 1300 546 747

WWW.LINQHS.COM

SINGLE LEG LANYARD HARDWARE



FOR COMPLETE CODE ADD LANYARD & HARDWARE CODE TOGETHER

EG. SINGLE LEG ADJUSTABLE LANYARD WITH 2 X TRIPLE ACTION KARABINERS = WLO1 + KTKT

KDKD >



2 x Double Action Karabiners

KDSD >



1 x Double Action Karabiner
1 x Double Action Scaff Hook

KDSN >



1 x Double Action Karabiner
1 x Snap Hook

KDST >



1 x Double Action Karabiner
1 x Triple Action Scaff Hook

KTKT >



2 x Triple Action Karabiners

KTSD >



1 x Triple Action Karabiner
1 x Double Action Scaff Hook

KTSN >



1 x Triple Action Karabiner
1 x Snap Hook

KTST >



1 x Triple Action Karabiner
1 x Triple Action Scaff Hook

SNKT >



1 x Snap Hook
1 x Triple Action Karabiner

SNSD >



1 x Snap Hook
1 x Double Action Scaff Hook

SNSN >



2 x Snap Hooks

SNST >



1 x Snap Hook
1 x Triple Action Scaff Hook

KSKD >



1 x Screw Gate Karabiner
1 x Double Action Karabiner

KSSN >



1 x Screw Gate Karabiner
1 x Snap Hook

KSSD >



1 x Screw Gate Karabiner
1 x Double Action Scaff Hook

KSST >



1 x Screw Gate Karabiner
1 x Triple Action Scaff Hook

KSKS >



2 x Screw Gate Karabiners

SNTSNT >



2 x Triple Action Snap Hooks

SNTST >



1 x Triple Action Snap Hook
1 x Triple Action Scaff Hook

SNGS >



1 x Snap Hook
1 x Giant Scaff Hook

Reading of LINQ instruction manual prior to use is mandatory. Description and specification subject to change without notice. If in doubt please contact the LINQ helpline.

AUS: 1300 546 747

NZ: 0800 546 747

INTERNATIONAL: +61 1300 546 747

WWW.LINQHS.COM